



BRINGING QUALITY TO THE SURFACE

**IRISH TAR**

## INTERFLEX (C70BP3)

### POLYMER MODIFIED EMULSION

**Interflex is a polymer modified emulsion bond coat/tack coat for bonding bituminous layers.**

#### PRINCIPAL APPLICATIONS

**Interflex** is especially recommended for the bonding of surface course layers e.g. hot rolled asphalt (HRA), porous asphalt, stone mastic asphalt (SMA) and thin layer surface courses (thin layer asphalt). It can also be used for the bonding of bituminous layers to cement bound bases, asphalt concrete, or macadam layers in road construction works.



#### ADVANTAGES OF USING INTERFLEX

- It contains heavy duty polymers which provide a strong adhesive bond between construction layers.

#### SPECIFICATIONS

It complies with IS EN 13808 and The National Roads Authority Binder Specifications for the requirements for bond coats for Porous Asphalt and Thin Layer surface courses.

**Interflex** is applied at a rate of 0.5 l/m<sup>2</sup>

**Recommended Temperature:**

Storage 75 to 85°C

**Interflex** complies with The NRA Binder Specifications: RC 380/13 Table 1.



**IRISH TAR**

**Available from**

Irish Tar & Bitumen Suppliers, Alexandra Road, Dublin 1

**Tel:** 01 855 5117 / **Fax:** 01 855 4262 / **Email:** info@irishtar.ie / **www.irishtar.ie**

Irish Tar & Bitumen Suppliers is registered to IS EN ISO 9001:2008 Quality Standard